



STYLE
3000

WEAVING
EXCELLENCE
WITH
INNOVATION



Code	Color	SOLAR OPTICAL PROPERTIES				SHGC/G VALUE	
		TS	RS	AS	TV	<i>SINGLE</i> 1/4 CL	<i>INSULATING</i> 1 HA
STYLE 3000 - 14%							
P01	Pearl White	24	62	14	21	0.33	0.23
Q01	Mushroom Sand	22	45	33	21	0.42	0.28
Q02	Custard Cream	23	53	24	22	0.37	0.26
Q04	Chocolate	13	4	83	15	0.63	0.38
Q17	Sand Dollar	17	46	37	15	0.41	0.27
Q18	Espresso	15	9	76	16	0.60	0.37
Q19	Honey Sage	16	31	53	16	0.49	0.31
V01	Pale Grey	19	40	41	19	0.44	0.29
V02	Ninja Grey	12	8	80	14	0.60	0.37



Microban® antimicrobial protection inhibits the growth of stain-causing bacteria, mold and mildew on the shade.



PRODUCT CERTIFIED FOR
LOW CHEMICAL EMISSIONS
UL.COM/GG
UL 2818



TS = Solar Transmittance
RS = Solar Reflectance
AS = Solar Absorption
TV = Visual Transmittance

SHGC = Solar Heat Gain Coefficient

1/4 CL = 1/4" Clear Glass
1 HA = 1" Heat Absorbing Glass

Fabrics Installed Internally
Zero-Degree Profile Angle

For additional performance values, test references and technical definitions visit us at www.phifer.com.

STYLE 3000 SPECIFICATIONS

Combining vinyl coated fiberglass and polyester yarns, Style 3000 is woven into a unique rib weave for a distinct look and color pallet. The 14% openness of Style 3000 lets in more natural light while providing excellent outward visibility. Style 3000 can also be used in exterior shading systems.

FIRE CLASSIFICATION	NFPA 701-2004 TM#1 (small scale) IBC Section 903.1 (Class A Rating) ASTM E 84 (Class 1)	NFPA 101 (Class A Rating) NFPA 701 TM#2 (large scale)
BACTERIA AND FUNGAL RESISTANCE	ASTM E 2180 ASTM G21 GREENGUARD Mold and Bacteria Standard ASTM 6329 includes Microban antimicrobial additives	AATCC30 Part 3 ASTM D 3273
ENVIRONMENTAL CERTIFICATION	GREENGUARD Certified to these standards for low chemical emissions into indoor air during product usage	GREENGUARD Gold
LEAD FREE	RoHS/Directive 2002/95/EC ANSI/WCMA A 100.1-2007 for lead content US Consumer Product Safety Commission Section 101	REACH (EC 1907/2006) compliant
WARRANTY	10-year interior 5-year exterior	
TRACKLESS	TrackLess Technology minimizes the fiberglass yarns' inherent tendencies to track when being rolled up in a shade. With TrackLess Technology these same fabrics now track less, roll up straighter and reduce shade fabrication time.	

STYLE 3000

WIDTHS	72" and 96" 182.9 cm and 243.8 cm
ROLL LENGTH	30 Linear Yards 27.4 m
COMPOSITION	35% Fiberglass, 65% Vinyl on Fiberglass 31% Polyester, 69% Vinyl on Polyester
MESH WEIGHT	13.46 oz/yd ² 456 g/m ²
FABRIC THICKNESS	0.028 in 0.71 mm
OPENNESS FACTOR	Approximately 14%
UV BLOCKAGE	Approximately 86%