



**SHEERWEAVE**  
BY PHIFER

STYLE  
7000

BLACKOUT FABRIC

---

WEAVING  
EXCELLENCE  
WITH  
INNOVATION



Code	Color	SOLAR OPTICAL PROPERTIES				SHGC/G VALUE	
		TS	RS	AS	TV	<i>SINGLE</i> 1/4 CL	<i>INSULATING</i> 1 HA
<b>STYLE 7000 - BLACKOUT</b>							
P62	White	0	64	36	0	0.27	0.21
V40	Onyx	0	64	36	0	0.27	0.21



PRODUCT CERTIFIED FOR  
LOW CHEMICAL EMISSIONS  
UL.COM/GG  
UL 2818



MIF Seal of Approval



TS = Solar Transmittance  
RS = Solar Reflectance  
AS = Solar Absorption  
TV = Visual Transmittance

SHGC = Solar Heat Gain Coefficient

1/4 CL = 1/4" Clear Glass  
1 HA = 1" Heat Absorbing Glass

Fabrics Installed Internally  
Zero-Degree Profile Angle

For additional performance values, test references and technical definitions visit us at [www.phifer.com](http://www.phifer.com).

# STYLE 7000 SPECIFICATIONS

Style 7000 is uniquely designed to provide total light blockage when complete room darkening is needed. With a broad range of decorator colors, the look and feel of rich cloth and a PVC-free composition, Style 7000 will enhance the beauty and function of both commercial and residential spaces. All Style 7000 colors have an off-white backing.

<b>FIRE CLASSIFICATION</b>	California U.S. Title 19 (small scale) BS 5867 2008 Part 2 Type B Performance ASTM E 84 (Class 1)	NFPA 701-2004 TM#1 (small scale) CAN/ULC-S 109-03 (large and small scale) CAN/CGSB2-4.162-M80
<b>BACTERIA AND FUNGAL RESISTANCE</b>	ASTM G21-96	AATCC 174-1998 Part II and III
<b>ENVIRONMENTAL CERTIFICATION</b>	GREENGUARD	GREENGUARD Gold Certified to these standards for low chemical emissions into indoor air during product usage
<b>LEAD FREE</b>	RoHS/Directive 2002/95/EC ANSI/WCMA A 100.1-2007 for lead content US Consumer Product Safety Commission Section 101	
<b>WARRANTY</b>	5-year interior	
<b>ACOUSTICAL PERFORMANCE</b>	NRC (Noise Reduction Coefficient) and SAA (Sound Absorption Average) tested in accordance with ASTM C423-09a	
<b>UV PROTECTION</b>	Seal of Approval by the Melanoma International Foundation (MIF) for effectiveness in preventing sun damage to the skin or eyes	
<b>CLEANING INSTRUCTIONS</b>	Fabric should be regularly dusted/vacuumed as appropriate. If commercial spot cleaners are used, they must first be tested and allowed to dry on an inconspicuous area to ensure compatibility. <i>Railroading this fabric is not recommended.</i> <i>Colors may vary slightly from swatch samples. All variations are within industry standards.</i>	

## STYLE 7000

---

<b>WIDTHS</b>	94" and 118" 238.8 cm and 299.7 cm
<b>ROLL LENGTH</b>	30 Linear Yards 27.4 m
<b>COMPOSITION</b>	100% Polyester with Acrylic Foamed Backing
<b>MESH WEIGHT</b>	13.41 oz/yd <sup>2</sup> 454.67 g/m <sup>2</sup>
<b>FABRIC THICKNESS</b>	0.026 in 0.66 mm
<b>OPENNESS FACTOR</b>	Opaque
<b>ACOUSTICAL VALUE</b>	NRC .10 / SAA .08