



STYLE
7500
BLACKOUT FABRIC

WEAVING
EXCELLENCE
WITH
INNOVATION



Code	Color	SOLAR OPTICAL PROPERTIES				SHGC/G VALUE g-tot (glass & blind)	
		TS	RS	AS	TV	SINGLE 1/4 CL	INSULATING 1 HA
STYLE 7500 - BLACKOUT							
R13	Ice	0	68	32	0	0.24	0.20
R22	Midnight	0	68	32	0	0.24	0.20



PRODUCT CERTIFIED FOR
LOW CHEMICAL EMISSIONS
UL.COM/GG
UL 2818



MIF Seal of Approval



TS = Solar Transmittance
RS = Solar Reflectance
AS = Solar Absorption
TV = Visual Transmittance

SHGC = Solar Heat Gain Coefficient

1/4 CL = 1/4" Clear Glass
1 HA = 1" Heat Absorbing Glass

Fabrics Installed Internally
Zero-Degree Profile Angle

For additional performance values, test
references and technical definitions visit us at
www.phifer.com.

STYLE 7500 SPECIFICATIONS

This attractive blackout fabric maintains high quality at an economical price. Style 7500 is presented in a classic range of neutral colors with a unique PVC-free composition. Ideal for commercial and residential applications, SheerWeave Style 7500 is an excellent option when total light blockage is needed. All 7500 colors have an off-white backing.

FIRE CLASSIFICATION	California U.S. Title 19 (small scale) CAN/ULC-S 109-03 (large and small scale)	NFPA 701-2004 TM#1 (small scale) ASTM E 84 (Class 1)
BACTERIA AND FUNGAL RESISTANCE	ASTM E 2180	ASTM G21
ENVIRONMENTAL CERTIFICATION	GREENGUARD	GREENGUARD Gold
	Certified to these standards for low chemical emissions into indoor air during product usage	
LEAD FREE	RoHS/Directive 2002/95/EC ANSI/WCMA A 100.1-2007 for lead content US Consumer Product Safety Commission Section 101	
WARRANTY	5-year interior	
ACOUSTICAL PERFORMANCE	NRC (Noise Reduction Coefficient) and SAA (Sound Absorption Average) tested in accordance with ASTM C423-09a	
UV PROTECTION	Seal of Approval by the Melanoma International Foundation (MIF) for effectiveness in preventing sun damage to the skin or eyes	
CLEANING INSTRUCTIONS	Fabric should be regularly dusted/vacuumed as appropriate. If commercial spot cleaners are used, they must first be tested and allowed to dry on an inconspicuous area to ensure compatibility.	

Railroading this fabric is not recommended.

Colors may vary slightly from swatch samples. All variations are within industry standards.

STYLE 7500

WIDTHS	78", 98" and 118" 198.1 cm, 248.9 cm and 299.7 cm
ROLL LENGTH	30 Linear Yards 27.4 m
COMPOSITION	100% Polyester with Acrylic Coating
MESH WEIGHT	12.14 oz/yd ² 412 g/m ²
FABRIC THICKNESS	0.014 in 0.356 mm
OPENNESS FACTOR	Opaque
ACOUSTICAL VALUE	NRC .00 / SAA .03